

| | SPM59 | SPM56 | Kingfisher KI 6106 |
|----------------------------|--------------|---------------------|--------------------|
| through mode | ✓ | ✓ | ✓ |
| λ down stream 1490/1577 nm | ✓ | ✓ | ✓ |
| Measurement Range | -40...+10dBm | -40...+12dBm | -45...+10dBm |
| Isolation | >35dB | >40dB | >40dB |
| λ up stream 1270/1310 nm | ✗ | ✓ | ✓ |
| Measurement Range | ✗ | -35...+10dBm | -30...+10dBm |
| Isolation | ✗ | >40dB | >40dB |
| Standard 1550 nm | ✓ | ✓ | ✗ |
| Measurement Range | -40...+26dBm | -40...+25dBm | ✗ |
| Isolation | >35dB | >40dB | ✗ |
| Uncertainty | ± 0.5 dB | ± 0.5 dB | ± 0.5 dB |
| Insertion Loss | ≤1.5dB | ≤1.5dB | ≤1.5dB |
| Alimentazione | 3xAA / Litio | Litio 4000mAh | Litio 1000mAh |
| data storage | ✗ | 1000 | 99 |
| Collegamento USB/BT | ✗ | ✗ solo per ricarica | USB-mini |
| Power adapter | ✗ | ✓ | ✓ |
| Manuale | ✓ | ✓ | ✓ |
| Borsa | ✓ | ✓ | ✓ |
| Software | ✗ | ✗ | ✓ in dotazione |
| Luce visibile | ✗ | ✓ | ✗ |
| funzionalità ethernet | ✗ | # | ✗ |

= misure di lunghezza cavo RJ45, sequenza conduttori, tracciavolto (300 m)